

Crash Therapy Promotions

Upperco VFC Demolition Derby

2020 Mini Van/Mini Truck/SUV Rules

1. Any Stock, Domestic or Foreign , 2 wheel drive, No FULL SIZE VANS. No, commercial or military type vehicles. Ford Explorer, Dodge Durango are allowed. Vehicle must be stock (see exceptions noted below.). Stock means manufactured showroom equipped including the same cylinder size, make/model for engine, transmission and differential components.
2. Drivers must have a valid state issued driver's license or ID Card.
3. Drivers under the age of 18 must have a consent form signed by parent or legal guardian
4. All drivers must complete registration and waiver forms at the time of registration.
5. Registration opens at 10am and close at 2pm. the day of the event. No Late cars.
6. All drivers and crew must attend the driver's meeting at 2:30pm the day of the event.
7. Anyone in the pit area must wear a wristband that will be given to you when all required waivers are signed.
8. Each competitor will be allowed one truck and trailer/service vehicle in the pit area. NO EXCEPTIONS!
9. Drivers and crew will register and pay at the pit gate and will be inspected in the pit area.
10. Alcohol is prohibited in the pits. Any speculation of drugs or alcohol use in the pits will result in an automatic disqualification and removal from the pit area.
11. NO DELIBERATE DRIVER'S DOOR HITS!!! The first deliberate hit will result in disqualification from the current event being run. If the drivers hits a second driver's door he will be disqualified for the rest of the night. INEVITABLY YOU WILL GET HIT IN THE DRIVER'S DOOR! IT'S A DEMOLITION DERBY, NOT A DRAG RACE!
12. When a driver is in the vehicle the safety belt must be fastened, DOT approved helmet with face shield or safety goggles must be worn.
13. A 5 MPH speed limit will be enforced anywhere on the grounds when not on the track.
14. All vehicles are subject to re-inspection at any time.
15. The driver may signal for medical attention by waving their hands. This action will result in a red flag and stop the race. Medical attention will be provided
16. Officials may require modifications to a vehicle at any time for safety reasons or rules.
17. All cars should come prepared. There will be no stripping of cars in the pit area. All drivers will be responsible for leaving with what you brought to the track.
18. The officials ruling or decision is final. Unsportsmanlike conduct will result in immediate disqualification and removal from grounds. Drivers are responsible for their crew. _
19. A 12" x 12" number plate must be mounted vertical on the roof of the vehicle. Number plate MUST be easy to read and be a contrasting color. (Maximum of 3 numbers or letters can be used)
20. Bumpers must be stock, or any car bumper may be used. Bumpers ends may be bent or cut. No commercial bumpers permitted. You may bolt bumper, limit 4 bolts per bumper, OR weld the bumper,

shock or mount. If welding, each bumper is allowed 12 inches of weld - 6 inches per side. These are the only alterations allowed.

21. DIFFERENTIALS Maybe welded or modified to create positive traction
22. If 4x4 or AWD you must remove one driveshaft, to make 2wd.
23. DOORS All MUST be chained shut. ONLY the driver's side doors may be REINFORCED and welded shut by using no more than 18-inches of vertical weld.
24. Drivers door maybe reinforced.
25. ENGINE MOTOR MOUNTS Engine may be secured to the frame by any method that does not strengthen any other components.
26. Battery may be re-located on the passenger side floor providing it is secured and completely covered.
27. Solenoid, voltage regulator, and other computer electronics, may be relocated, provided they remain under the hood and forward of the front firewall.
28. All air bags and activation charges must be disconnected and removed.
29. EXHAUST PIPES May remain STOCK and extend beyond the driver's seat or stacks will be permitted through the hood a maximum of 12" high
30. FAN BLADE: MUST be a electric fan and may be of any make or model. Clutch fans MUST be removed.
31. FENDERS AND INNER/OUTER WHEEL WELLS MUST be in place, cutting, folding or bending is permitted. Plastic inner wheel wells maybe removed.
32. . GAS TANK MAY be stock and remain in original position. Factory tanks located inside the vehicle will be permitted. If an approved inside alternate fuel tank is installed, like the ones used with outboard marine engines, the factory tank must be removed. Tank must be located in the center of the vehicle by the back seat area if not using the stock tank . All inside gas tanks must secured through the bed or floor of the vehicle.
33. GLASS All glass MUST be removed, including headlights, plastic taillights, bulbs, mirrors. Broken glass anywhere in the vehicle (doors, body panels, etc.) must be removed or the vehicle will not be admitted. WINDSHEILDS MAY REMAIN.
34. HEATING/COOLING SYSTEM Radiator may be bypassed, but MUST remain in original position with NO reinforcement. All antifreeze must

be drained and replaced with water. Heater system may be bypassed or removed.

35. HOOD AND TAILGATE/BACK DOORS MUST BE IN PLACE may have 2 vertical hood bars (To prevent hood from entering the driver's compartment) in the front window IF WINDSHEILD IS REMOVED . FIRE REGULATION - To prevent hoods and tailgates from opening, each must be tied down in 2 positions after inspection. Tailgate/Back doors may be welded with a maximum of 4 - 4 inch welds. Use no more than 2 strands of #9 wire on each, or (1)24-inch long by ¼-inch maximum link diameter chain or smaller on each. The chains must have 1 link of slack and cannot reinforce any other part of the vehicle.
36. FIRE REGULATION A hole must be cut in the hood 1-foot to the side of the center and no larger than 8 inches in diameter. Hood and tailgate/rear hatch hinges must remain hooked up but all springs must be disconnected.
37. IGNITION SWITCH: (HOT WIRING) Complete ignition switch may be relocated and/or altered providing key or toggle switches are painted white and accessible within 16 inches of the steering wheel.
38. INTERIOR/EXTERIOR ALL carpet, visors and rear seat cushions MUST be removed. (Front passenger seat must remain in place.) Exception: If front passenger seat is removed, a bar must be installed from the driver's door to the passenger door, directly behind the front seat for extra support. It is recommended that driver's door panel upholstery be left in place, driver's side padding is required. Fiberglass/plastic front/rear clip and grill parts and all loose materials, mirrors, wheel covers, sharp hood ornaments, trailer hitch, hitch brackets, running boards and all soft chrome molding MUST be removed. All dirt and loose pieces of glass MUST be swept/vacuumed out of vehicle and doors.
39. All sunroofs must have glass removed and covered/fastened with sheet metal of same strength as roof material.
40. Suspension MUST be factory soft and move up and down freely a total of 4 inches by one man's effort. Vehicle MUST sit at stock height, (maximum 20 inches from the ground to the center of the stock front and rear bumper.) Frozen shocks are illegal.
41. TIRES ANY DOT APPROVED TIRES UP TO 6 PLY ONLY! AIR ONLY - NO liquids or solids. ALL wheel weights inside and out MUST be removed.
42. TRANSMISSION: You will be permitted to alter and relocate shifting method of transmission from factory stock. Also, to stop shifting linkage from coming off, it is recommended to wire, clip, tack

weld or change linkage to prevent this. The transmission lines may be bypassed; transmission cooler must remain under the body/hood.

43. **WE HAVE THE RIGHT TO RE-INSPECT, CUT, OR DRILL ANY CAR AT ANY TIME. IF YOU ARE CAUGHT BREAKING THE RULES SET HERE FORTH YOU WILL FORFEIT ANY AND ALL WINNINGS AND OR PRIZES YOU ARE DUE.**

REMEMBER IF ITS A GREY AREA FOR YOU ITS PROBABLY A BLACK AREA FOR US SO DON'T DO IT !!!

Any Questions call/text Dave Caltrider 443-375-8294